


# Pantanet<sup>®</sup> Essential & Light

## Welded mesh

The Pantanet Essential & Light system are welded, galvanised and plastic coated fences on rolls, designed for optimal price-quality ratio.

## **Product detail**



### **BENEFITS**

### **Aesthetic and discreet**

The fence is available in green. The Pantanet Essential range is also available in metallic anthracite.

### **High longevity**

The wire is plastic coated with maximum adhesion. The metal posts are galvanised inside and outside, passivated and plastic coated, and supplied complete with top caps.

## **Quick and professsional installation**

Bekaclip posts with strips guarantee a quick professional installation with an optimal tensioned mesh.

### **Complete system**

Pantanet system is a complete system with a wide range of roll heights, posts and a wide assortment of swing gates.

# **Security level**



# **Applications**



# **Functionalities**



### Mesh

Welded mesh, plastic coated. The horizontal wires show a crimp at every mesh. At 25,4 mm from the top, the mesh is reinforced with a second selvedge wire (only Pantanet Essential).

### Coating technique

The rolls are PVC coated.



#### Gates

The Pantanet system can be completed with the Fortinet and Robusta swing gates and the Robusta sliding gates.

### Colours

Fence: green BF 6073 or metallic anthracite\* (BF7016M)

Posts: green RAL 6005 or metallic anthracite\*\* (BF7016M)

#### Installation

### Bekaclip posts (for green and anthracite)

Round steel posts. The straining and intermediate posts have a mesh fixing strip and are supplied with plastic top caps. The fixing clips are of stainless steel. (Bekaclip posts in anthracite for do-it-yourself-installation are available with anthracite polyamide clips.)

### **Round Steel Posts**

In and outside galvanised with a min. layer thickness of 275 g/m2 (2 sides combined) following Euro standard EN 10346. Galvanised and plastic coated with polyester with a min. layer thickness of 60 micron.

MESH DIMENSIONS OF PANTANET ESSENTIAL & LIGHT									
		Diamet	ter wire	Tensile strength of the wire					
Туре	Mesh dimensions mm	Horizontal mm	Vertical mm	Horizontal	Vertical				
Pantanet Essential	101,60 x 50,80	2,1	2,2	min. 400 N/mm²	min. 700 N/mm²				
Pantanet Light	101,60 x 76,20	2,1	2,1	min. 400 N/mm²	min. 700 N/mm²				

<sup>\*</sup> Pantanet Essential is also available in anthracite, for some heights.

METAL ROUND & BEKACLIP POSTS												
			Straining posts Bekaclip			Round brace posts			Intermediate posts Bekaclip			
	Total height Fence		Length	Ø mm	Thickness steel	Length	Ø	Thickness steel	Length	Ø	Thickness steel	
Essential	Light	Essential	Light	mm	"""	piate IIIII	mm	mm	plate mm	mm	mm	plate mm
610	600	610	600	1100	48	1,2	1500	38	1,25	1100	48	1,2
810	800	810	800	1100	48	1,2	1500	38	1,25	1100	48	1,2
1020*	1000	1020*	1000	1500	48	1,2	1500	38	1,25	1500	48	1,2
1220*	1200	1220*	1200	1700	48	1,2	1750	38	1,25	1700	48	1,2
1520*	1500	1520*	1500	2000	48	1,2	2200	38	1,5	2000	48	1,2
1830	₹:	1830	-	2500	60	2	2700	38	1,5	2300	48	1,5
2030		2030	-	2700	60	2	2700	38	1,5	2500	48	1,5

Lenght of rolls: 25 m - for some types also 10 m \* Also available in grey anthracite BF7016M

Europe Blokkestraat 34b B-8550 Zwevegem

Tel: B: +32 56 73 46 46 Tel: NL: 0800 022 76 98 USA 3309 SW Interstate 45 Ennis, TX 75119

Tel: +1 972 878 7000

Middle East P.O. Box 293517 DAFZA, Building E 5, Block A 8th Floor, Office 802 Tel: +971 04 6091122 Africa B10, Bergriver Business Park Paarl, 7646

Tel: +27 021 868 7300